


230-2010

Nylon Screw Plugs (Blind Plugs)

Metric PG G (PF)



Thread	Cat. No.	Cat. No.			Dimensions		Std. Pkg. pcs	
		Sizes	Black RAL 9005	Light Grey RAL 7035	Silver Grey RAL 7001	A mm		B mm
M12 X 1.5	SPG - M12	B	G	SG	6.5	16	100	
M16 X 1.5	SPG - M16	B	G	SG	8	20	100	
M20 X 1.5	SPG - M20	B	G	SG	8	25	100	
M25 X 1.5	SPG - M25	B	G	SG	8.5	30	100	
M32 X 1.5	SPG - M32	B	G	SG	10	38	50	
M40 X 1.5	SPG - M40	B	G	SG	13	47	50	
M50 X 1.5	SPG - M50	B	G	SG	14	57	10	
M63 X 1.5	SPG - M63	B	G	SG	15	70	10	
PG 7	SPG - PG7	B	G	SG	6.5	16	100	
PG 9	SPG - PG9	B	G	SG	6.5	19	100	
PG 11	SPG - PG11	B	G	SG	6.5	22.5	100	
PG 13.5	SPG - PG13.5	B	G	SG	7	25.2	100	
PG 16	SPG - PG16	B	G	SG	8	27.5	100	
PG 21	SPG - PG21	B	G	SG	9	34	100	
PG 29	SPG - PG29	B	G	SG	8.5	44.6	50	
PG 36	SPG - PG36	B	G	SG	11	55	50	
G (P F)	1/4	SPG - PF13	B	G	SG	6.5	17	100
	3/8	SPG - PF17	B	G	SG	8	20.5	100
	1/2	SPG - PF21	B	G	SG	8	26	100
	3/4	SPG - PF26	B	G	SG	10	32	100
	1	SPG - PF33	B	G	SG	12	40	50
	1 1/4	SPG - PF42	B	G	SG	13	49	50

- Thread Type : Metric, PG and G (PF).
- Material Data : Halogen-free Nylon PA 66 (Flammability UL 94V-2) ; Contact us for V0 material.
- IP Protection : IP68 (when assembled with AVC's hard twist washer)
IP67 (when assembled without washer on the very plane surface).
- Working Temp. : - 40 °C to 105 °C (- 40 °F to 221 °F). Short-Term to 160 °C (320 °F).
- Application : IP protection for spare holes :
1. Polyamide Blind Plugs are used where existing threaded holes need to be closed.
2. Assembled with AVC's Lock Nuts for closing the holes without thread.

* For AVC's High quality Lock Nuts, please refer to category 230-3010.
* For AVC's High quality twist-resistance Washers, please refer to category 230-4010.

