

230-3010 P-LG Nylon Lock Nuts (Counter Nuts)

Metric PG G (PF)



Thread	Cat. No.	Cat. No.			Height mm	Spanner Sizes mm	Std. Pkg. pcs	
		Sizes	Black RAL 9005	Light Grey RAL 7035				Silver Grey RAL 7001
M8 X 1.25	P - LG - M8	B	G	SG	5	13	50	
M10 X 1.5	P - LG - M10	B	G	SG	5	15	50	
M12 X 1.5	P - LG - M12	B	G	SG	5	18	50	
M16 X 1.5	P - LG - M16	B	G	SG	6.5	22	50	
M20 X 1.5	P - LG - M20	B	G	SG	6.5	27	50	
M25 X 1.5	P - LG - M25	B	G	SG	7	33	50	
M32 X 1.5	P - LG - M32	B	G	SG	7.5	41	10	
M40 X 1.5	P - LG - M40	B	G	SG	10	50	10	
M50 X 1.5	P - LG - M50	B	G	SG	10	62	10	
M63 X 1.5	P - LG - M63	B	G	SG	11	75	10	
M75 X 2	P - LG - M75	B	G	SG	9.5	92	2	
M90 X 2	P - LG - M90	B	G	SG	10	110	2	
PG 7	P - LG - PG7	B	G	SG	5	17	50	
PG 9	P - LG - PG9	B	G	SG	6	22	50	
PG 11	P - LG - PG11	B	G	SG	6	24	50	
PG 13.5	P - LG - PG13.5	B	G	SG	6	27	50	
PG 16	P - LG - PG16	B	G	SG	6.5	30	50	
PG 21	P - LG - PG21	B	G	SG	7	36	50	
PG 29	P - LG - PG29	B	G	SG	8	46	10	
PG 36	P - LG - PG36	B	G	SG	8	57	10	
PG 42	P - LG - PG42	B	G	SG	9	64	10	
PG 48	P - LG - PG48	B	G	SG	9	70	10	
G (P F)	1/4	P - LG - PF13	B	G	SG	5.5	19	50
	3/8	P - LG - PF17	B	G	SG	6	22	50
	1/2	P - LG - PF21	B	G	SG	6.5	27	50
	3/4	P - LG - PF26	B	G	SG	6.5	33	50
	1	P - LG - PF33	B	G	SG	7	42	10
	1 1/4	P - LG - PF42	B	G	SG	7.3	53	10
	1 1/2	P - LG - PF48	B	G	SG	8	57	10
	2	P - LG - PF60	B	G	SG	9	70	10
	3	P - LG - PF88	B	G	SG	10	110	2

- Thread Type : Metric, PG and G (PF).
- Material Data : Halogen-free Nylon PA 66 (Flammability UL 94V-2).
* Contact us for Flammability V0 material.
- Working Temp. : - 40 °C to 105 °C (- 40 °F to 221 °F).
Short-Term to 160 °C (320 °F).
- Application : Hexagonal polyamide counter nuts with thread are matched with AVC Cable Glands or Blind Plugs, which are required when Glands or Plugs have to be countered to fit the housing holes without thread.

230-3020 P-LB Brass Lock Nuts (Counter Nuts)

Metric PG G (PF)



Thread	Cat. No.	Height mm	Spanner Sizes mm	Std. Pkg. pcs	
					M6 X 1
M8 X 1.25	P - LB - M8	2.8	11	10	
M10 X 1.5	P - LB - M10	2.8	13	10	
M12 X 1.5	P - LB - M12	3.6	17	10	
M16 X 1.5	P - LB - M16	4.5	22	10	
M20 X 1.5	P - LB - M20	4.5	26	10	
M25 X 1.5	P - LB - M25	4.5	32	10	
M32 X 1.5	P - LB - M32	4.5	41	10	
M40 X 1.5	P - LB - M40	5	50	5	
M50 X 1.5	P - LB - M50	5	60	2	
M63 X 1.5	P - LB - M63	5	73	2	
M75 X 2	P - LB - M75	5	85	1	
M90 X 2	P - LB - M90	5.5	106	1	
M100 X 2	P - LB - M100	7	120	1	
PG 7	P - LB - PG7	3.6	17	10	
PG 9	P - LB - PG9	3.6	18	10	
PG 11	P - LB - PG11	4.5	22	10	
PG 13.5	P - LB - PG13.5	4.5	24	10	
PG 16	P - LB - PG16	4.5	26	10	
PG 21	P - LB - PG21	4.5	32	10	
PG 29	P - LB - PG29	4.5	41	10	
PG 36	P - LB - PG36	5	50	5	
G (P F)	1/4	P - LB - PF13	3.6	17	10
	3/8	P - LB - PF17	4.5	22	10
	1/2	P - LB - PF21	4.5	26	10
	3/4	P - LB - PF26	4.5	32	10
	1	P - LB - PF33	4.5	41	10
	1 1/4	P - LB - PF42	5	50	5
	1 1/2	P - LB - PF48	5	60	2
	2	P - LB - PF60	5	73	2
	2 1/2	P - LB - PF75	5	85	1

- Thread Type : Metric, PG and G (PF).
- Material Data : Brass nickel-plated (JIS C3604 / DIN CuZn39Pb3 / ASTM C37800).
- Application : Hexagonal brass counter nuts with thread are matched with AVC Cable Glands or Blind Plugs, which are required when Glands or Plugs have to be countered to fit the housing holes without thread. The nickel-plated Brass provides the excellent mechanical properties.