



## 230-4010 Rubber Washers (Gaskets)



For Sizes	Cat. No.		I. D.	O. D.	Thickness	Std. Pkg.	
	EPDM	NBR	mm	mm	mm	pcs	
M 8	P - WE - M8	P - WN - M8	8	12.5	1.6	50	
M 10	P - WE - M10	P - WN - M10	10	14.5	1.8	50	
M 12	P - WE - M12	P - WN - M12	12	20	1.4	50	
M 16	P - WE - M16	P - WN - M16	16	24	1.7	50	
M 20	P - WE - M20	P - WN - M20	20	28	1.7	50	
M 25	P - WE - M25	P - WN - M25	25	35	1.7	50	
M 32	P - WE - M32	P - WN - M32	32	44	1.7	10	
M 40	P - WE - M40	P - WN - M40	40	52	1.8	10	
M 50	P - WE - M50	P - WN - M50	50	65	1.8	10	
M 63	P - WE - M63	P - WN - M63	63	80	1.8	10	
M 75	P - WE - M75	P - WN - M75	74.5	92	2	2	
M 90	P - WE - M90	P - WN - M90	89	110	2	2	
M 100	P - WE - M100	P - WN - M100	99	120	2	2	
PG 7	P - WE - PG7	P - WN - PG7	12.3	16	1.4	50	
PG 9	P - WE - PG9	P - WN - PG9	15	20	1.4	50	
PG 11	P - WE - PG11	P - WN - PG11	18	26	1.7	50	
PG 13.5	P - WE - PG13.5	P - WN - PG13.5	20	28	1.7	50	
PG 16	P - WE - PG16	P - WN - PG16	22.5	29.5	1.7	50	
PG 21	P - WE - PG21	P - WN - PG21	28	35.5	1.7	50	
PG 29	P - WE - PG29	P - WN - PG29	37	45	1.8	10	
PG 36	P - WE - PG36	P - WN - PG36	47	54	1.8	10	
PG 42	P - WE - PG42	P - WN - PG42	54	65	1.8	10	
PG 48	P - WE - PG48	P - WN - PG48	59	70	1.8	10	
G (PF)	1/4	P - WE - PF13	P - WN - PF13	13	18	1.4	50
	3/8	P - WE - PF17	P - WN - PF17	16	24	1.7	50
	1/2	P - WE - PF21	P - WN - PF21	20	28	1.7	50
	3/4	P - WE - PF26	P - WN - PF26	26	34	1.7	50
	1	P - WE - PF33	P - WN - PF33	33	43	1.7	10
	1 1/4	P - WE - PF42	P - WN - PF42	42	53	1.8	10
	1 1/2	P - WE - PF48	P - WN - PF48	48	60	2	10
	2	P - WE - PF60	P - WN - PF60	59	70	2.4	10
	2 1/2	P - WE - PF75	P - WN - PF75	74.5	92	2	2
3	P - WE - PF88	P - WN - PF88	86	110	2	2	

- Material : Weather-resistant EPDM rubbers & Oil-resistance NBR rubbers.
- Color : Black.
- Application : To fix with Metric, PG and G ( PF ) glands or similar parts, provide safe sealing against dust, water and oil on the fastening thread of the connector to the housing.

## 230-5010 EMC Brass Earth Tags (Customized)



For Sizes	Cat. No.	A	B	Thickness	Std. Pkg.
		mm	mm	mm	pcs
M 12	P - ET - M12	12	Customized	1.4	50
M 16	P - ET - M16	16	Customized	1.7	50
M 20	P - ET - M20	20	7	1.7	50
M 25	P - ET - M25	25	10.5	1.7	50
M 32	P - ET - M32	32	12.2	1.7	10
M 40	P - ET - M40	40	13.5	1.8	10
M 50	P - ET - M50	50	13.5	1.8	10
M 63	P - ET - M63	63	13.5	1.8	10
M 75	P - ET - M75	75	13.5	2	2
M 90	P - ET - M90	90	14	2	2
M 100	P - ET - M100	100	14	2	2

- Material : Brass ( JIS C3604 / DIN CuZn39Pb3 / ASTM C37800 )  
Consult us for nickel-plating ( If required ).  
\* For use with AVC metal cable glands in Metric thread.
- Application : Hi-End Brass Earthing Tag connected with Metal Gland and Equipment or Earth Wire helps to achieve an optimum EMC bonding to withstand electromagnetic interference, providing continuous EMC protection.