

250-8010 Tubing Holders



- Material Data : UL- certified Nylon PA 66 (Flammability UL 94V-2).
- Working Temp. : - 40 °C to 105 °C (- 40 °F to 221 °F). Short-Term to 160 °C (320 °F).
- Application : The refined polyamide tubing holders are easily used with any common corrugated conduits and tubings vertically or horizontally, to secure tubings in place. This product series can mount the common sizes of conduits (1/4" - 2") with strong fastening performance for outdoor / indoor applications.

* Recommended distance between brackets at intervals not greater than 3 feet (914 mm) as required by Article 351-27 of 1996 NEC.

* For European Standard EN 50343 : 2003, recommended distance between brackets at intervals not greater than 300 mm (Horizontal wiring) & 500 mm (Vertical wiring).

Cat. No.			Tubing O.D. mm φ	Accommodated AVC Tubings				Fixing	Std. Pkg.
Sizes	Black RAL 9005	Silver Grey RAL 7001		NYLON		HDPE		Screw	pcs
N - TH - 10	B	SG	10	(NGN - 07B)	1/4 "	(NFE - 02B)	1/4 "	M 4	50
N - TH - 13	B	SG	13	(NGN - 10B)	5/16 "	(NFE - 02.5B)	5/16 "	M 5	50
N - TH - 15	B	SG	15.8	(NGN - 12B)	3/8 "	-	-	M 5	50
N - TH - 18	B	SG	18.3	(NGN - 14B)	3/8 "	(NFE - 03B)	3/8 "	M 5	50
N - TH - 21	B	SG	21.2	(NGN - 17B)	1/2 "	(NFE - 04B)	1/2 "	M 6	50
N - TH - 26	B	SG	26	(NGN - 22B)	3/4 "	(NFE - 06B)	3/4 "	M 6	50
N - TH - 28	B	SG	28.5	(NGN - 23B)	3/4 "	-	-	M 6	50
N - TH - 34	B	SG	34.5	(NGN - 28B)	1 "	(NFE - 08B)	1 "	M 6	10
N - TH - 42	B	SG	42.5	(NGN - 36B)	1 1/4 "	(NFE - 10B)	1 1/4 "	M 6	10
N - TH - 48	B	SG	48	(NGN - 40B)	1 1/2 "	(NFE - 12B)	1 1/2 "	M 6	10
N - TH - 54	B	SG	54.5	(NGN - 47B)	2 "	-	-	M 6	10
N - TH - 60	B	SG	60	(NGN - 52B)	2 "	(NFE - 16B)	2 "	M 6	10

250-8020 Plastic Corrugated Tubings Outlet Bushings (Ferrules)

PATENTED



- Material Data : Weather-resistant EPDM Rubber. (Contact us for ordering NBR rubber in oil-resistance applications)
- Working Temp. : Up to 125 °C (257 °F).
- Application : In order to protect cables from contacting the sharp edged tubings, the smart & refined rubber ferrules are designed to protect edges of tubings without using a connector. Due to its simple design, installation is quickly with some water moistened effects and simply snaps onto the corrugated tubing edges (with outside diameters from 10 to 89 mm can be mounted). AVC's high-grade rubber ferrules are with good performance in weather resistance, which are the protectors for cable entries or outlets of machine construction and equipment installation.

Cat. No.		Tubing O.D. mm φ	Accommodated AVC Tubings				Std. Pkg.
Sizes	Black		NYLON		HDPE		pcs
N - TB - 10	B	10	(NGN - 07B)	1/4 "	(NFE - 02B)	1/4 "	50
N - TB - 13	B	13	(NGN - 10B)	5/16 "	(NFE - 02.5B)	5/16 "	50
N - TB - 15	B	15.8	(NGN - 12B)	3/8 "	-	-	50
N - TB - 18	B	18.3	(NGN - 14B)	3/8 "	(NFE - 03B)	3/8 "	50
N - TB - 21	B	21.2	(NGN - 17B)	1/2 "	(NFE - 04B)	1/2 "	50
N - TB - 26	B	26	(NGN - 22B)	3/4 "	(NFE - 06B)	3/4 "	50
N - TB - 28	B	28.5	(NGN - 23B)	3/4 "	-	-	50
N - TB - 34	B	34.5	(NGN - 28B)	1 "	(NFE - 08B)	1 "	10
N - TB - 42	B	42.5	(NGN - 36B)	1 1/4 "	(NFE - 10B)	1 1/4 "	10
N - TB - 48	B	48	(NGN - 40B)	1 1/2 "	(NFE - 12B)	1 1/2 "	10
N - TB - 54	B	54.5	(NGN - 47B)	2 "	-	-	10
N - TB - 60	B	60	(NGN - 52B)	2 "	(NFE - 16B)	2 "	10
N - TB - 88	B	89	(NGN - 72B)	3 "	-	-	2